



Minimess Nitrogen Gas Charging & Testing Kit 540I-02-00.KIT

- Safe & easy to use Minimess® charging & testing connections
- Designed to connect to Minimess charging valves & adaptors
- Minimess test points offer excellent system access versatility
- Simple hand tightening hose connection on to accumulator charging device
 - High quality pressure regulator for quick and accurate testing, reducing or charging with nitrogen



The Minimess® gas charging test kit is the ultimate service tool designed to test, reduce or increase charge pressures in accumulators fitted with Minimess charging or testing connections.

Industrial accumulators

Mobile plant

Wind turbines

Fire suppression

Military vehicles

MINIMESS®

Gas Charging Kits & Accessories

5401-02-00.KITX

The Minimess® nitrogen accumulator charging kit with pressure regulator is designed for charging or testing accumulators fitted with Minimess 1615 or 1620 series valves with nitrogen. The kit has a choice of additional valves & adaptors if required and comes with a high quality pressure regulator for setting charge pressures making this the ultimate tool for servicing Minimess charging systems.

FEATURES

- Safe & easy to use Minimess® charging & testing connections
- Allows connection to most common accumulators
- Minimess 1615 or 1620 accumulator connections
- M28x I.5 female accumulator connection with additional 5/8" 18 UNF, VG8 (schrader style), 7/8" - 14 UNF and 1/4" BSP adaptors
- High quality bottle pressure regulation for setting of charge pressures from 10 to 235 bar

KIT CONTENTS

- 1 x 5401-02-00.00 nitrogen pressure regulator with W24,32x 1/14" female (European Standard) nitrogen bottle connection with additional 5/8" BSP UK bottle adaptor. 10...235 bar settable pressure range.
- 1 x 250 bar analogue gauge for accumulator pressure (digital on request) & 400 bar analogue gauge for gas bottle pressure.
- 1 x Minimess 1615 to Minimess 1615 (with check valve) microbore charging & testing 2.5 metres long
- 1 x Minimess 1615 to Minimess 1620 (with check valve) microbore charging & testing 2.5 metres long
- 1 x Minimess 1615 charging valve to 1/4" BSP male (Kit 1).
- 1 x Minimess 1615 adaptor to 7/8" 14 UNF female (Kit 2).
- 1 x Minimess 1615 adaptor to M28x1.5 female (Kit 3).
- 1 x Minimess 1615 adaptor to VG8 (schrader style valve) female (Kit 4).

MINIMESS® CHARGING VALVE OPTIONS



Kit I

Minimess 1615 to GI/4" BSP male



Minimess 1615 to 7/8" - 14 UNF female. (Requires removal of original valve)



Minimess 1615 to M28x 1.5 female. (Requires removal of original valve)

Kit 4



Minimess 1615 to 5/16"-32 UNEF / Vg8 female (Schrader style)

CONNECTION EXAMPLES



ORDER CODE	
5401-02-00.KITX	
- 1	Minimess 1615 charging valve G1/4" male
2	Minimess 1615 to 7/8" - 14 UNF adaptor *
3	Minimess 1615 to M28x1.5 adaptor *
4	Minimess 1615 to VG8 (Schrader style)
	* 7/8-14 UNF and M28x1.5 options are permanent replacements only and require removal of original valve before fitting.

Replace X with charging adaptor code number required from table above Order with U suffix to receive complete adaptor set shown above Order with \times for no charging valve adaptor

Kit X



Minimess M16 x 2 (1620)

