



Bulkhead Adaptors




Thread (G)	p max	Connection	Part-Number
<i>G</i>	<i>Bar</i>		
16 x 1.5	630	On both sides for series 1615	2102-04-01.00

Pressure gauge connection for bulkhead fitting




Internal thread	p max	Connection	L	SW	Note	Part number
<i>G</i>	<i>Bar</i>		<i>mm</i>	<i>mm</i>		
ISO 228-G ¼	630	1615 / M 16 x 1.5	38	19	Without return valve	2102-05-11.00
ISO 228-G ½	630	1615 / M 16 x 1.5	42.5	27	Without return valve	2102-05-12.00

Pressure gauge – direct connection



Internal thread	p max	L	SW	Part number
<i>G</i>	<i>Bar</i>	<i>mm</i>	<i>mm</i>	
ISO 228-G ¼	630	14.5	19	2102-07-11.62
ISO 228-G ½	630	17	27	2102-07-12.62
¼ NPT	630	–	19	2102-07-23.62


90° Swivel screw connection



Thread	p max	L ₁	L ₂	SW	Part number
<i>G</i>	<i>Bar</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	
ISO 228-G ¼	630	43	69.5	19	2115-22-24.00

Sealing on screw-in thread (hollow screw) via dka-ring, on hexagon via Gi-ring (NBR).
Other options on request.

Hose Adaptors



Thread	p max	L	SW	Note	Part number
<i>G</i>	<i>Bar</i>	<i>mm</i>	<i>mm</i>		
M 16 x 1.5	630	42	17	Without return valve	2146-10-00.00

Other materials, further options, sealing and screw-in threads on request.