

## **BSP** Inline Test Point Tee Adaptors

BSP Parallel male x swivel female ( $60^{\circ}$  cone sealing) test point adaptor c/w I 620 Minimess <sup>TM</sup> test point fitted.

In line SNA Minimess® pressure test point adaptors are a simple and easy method of adding test points into a system.

Suitable for OEM build or retro-fitting to existing systems, SNAs fit between hose joints or manifold and hose.


Special configurations are available for OEM applications. Call for details.

Also available in JIC, ORFS & Metric formats.



## **FEATURES:**

- Test under pressure using Hydrotechnik leak free minimess connections up to 630 bar.
- Connect & disconnect under full system pressure.
- In-line test point tees offer excellent system access versatility.





Now available in stainless steel

## **BSP** Format

Α	L(mm)	A/F(mm)	Part number	Part number
1/4"	48	25.4	SNA01	SNA01-SS
3/8"	54	25.4	SNA02	SNA02-SS
1/2"	58	27	SNA03	SNA03-SS
3/4"	64	27	SNA04	SNA04-SS
5/8"	63	30	SNA05	on request
1"	74	41	SNA06	SNA06-SS
11/4"	74	50	SNA07	on request
11/2"	82	55	SNA08	on request

Also available with 1215 & 1615 test points fitted e.g for 1215 series test point fitted to SNA01- order as SNA01-1215.





