

Watchlog Bluetooth digital pressure gauges WLB-DPG

TECHNICAL CHARACTERISTICS

- The dial can be rotated 330°
- ✓ Large LCD screen, with multiple selectable pressure units
- Zero reset, backlight, Bluetooth connection to iOS and Android apps with datalogging
- Low power consumption design, 2x AA batteries, 12 months battery life
- Ergonomic & robust design, with rubber shroud and easy operation

WLB-DPG Watchlog bluetooth digital pressure gauges icorporate a high precision pressure sensor with an accurate LCD display showing measured pressure in real time and can transmit readings up to 100ms via Bluetooth.

This digital pressure gauge is equipped with a large size LCD liquid crystal display, which has multiple functions such as zero reset, backlight, power on and off, pressure unit selection & low voltage alarms.

Easy to operate and install, the display can be rotated 330° which is convenient for operators to read from different angles. The unit is supplied with a protective rubber shroud has good shock resistance and can measure gas, liquid, oil and other media that are not corrosive to stainless steel. This WLPB-DPG supports iOS and Android Bluetooth apps with configuration parameters that include display of pressure values, acquisition rate modification, zero reset operation, start/stop logging & export of csv test files. Watchlog Bluetooth digital pressure gauges are suitable for portable pressure measurement, equipment matching, calibration equipment and other pressure measurement fields.






TECHNICAL SPECIFICATIONS

Ranges	Negative/compound pressure Low pressure (on request)	Vacuum to & 6 bar 0 0.1, 0.4 & 0.6 bar	10.0
	Medium pressure	0 60, 160 & 250 bar	60
	High Pressure	0 400, 700 & 1000 bar	4.0
Overload Capacity	200% FS		20
Backlight colour	White		0.0
Dimensions	143.5 x 75 x 40.5mm		-47dBm 100% 0.00 - 600.00bar 1s
Accuracy	0.5%FS 0.2%FS (on request)		Downloadable iOS and Android apps for pressure display and logging
Long-term Stability	Typical ±0.3% FS/year		, 35 5
Operating Temperature	-2065°C		
Electrical protection	Anti-electromagnetic interference design		
Measuring medium	Oil, water, gas and other stainless steel corrosion free medium		
Pressure Connection	G1/4" BSP (alternative threads on request)		
Connection material	TPE+ABS		
Shell material	Wi-Fi, 4G LTE CAT-I, GNSS		
Product Features	Turn on/off, backlight, clear, zero unit, switch extreme value, record, Bluetooth connection		
Power supply voltage	3V (2x AA batteries)		
Power display	Four sections display		
Dial	Rotatable to 330 degrees		
Pressure unit	MPa, bar, kgf, mH20, PSI, kPa, mmHg, mBAR, mmH20, Pa, inWC		
Protection level	IP54		




DIMENSIONS

Units in mm







ORDERING CODE

WLB - DPG - XXXX

Range		Replace XXXX with	
-Ito Ibar		V001	
-I to I6 bar		V016	
0 to 60 bar		0060	
0 to 160 bar		0160	
0 to 250 bar		0250	
0 to 400 bar		0400	
0 to 700 bar		0700	
0 to 1000 bar		1000	



